

PED-AAK Ceiling concealed

Models				PED-3AAK		PED-5AAK		
Cooling capacity	50Hz	W		7,500		12,400		
		BTU/h		25,600		42,300		
Total input			kW	3.36		4.39		
Indoor unit	Model name			PED-3AAK		PED-5AAK		
	External finish			Galvanized sheets				
	Fan motor output			kW	0.09		0.10 + 0.14	
	Airflow (low-high)	50Hz	CMM		15-20		27-34	
			CFM		530-705		955-1,202	
	External static pressure			Pa (mmAq)	50/5		50/95	
	Operation control & thermostat			Remote controlled & Built-in				
	Noise level (low-high)	50Hz		dB (A)	38-42		40-44	
	Unit drain pipe thread			R1				
	Dimensions	W		mm	1,313		1,721	
		D		mm	740		740	
		H		mm	270		270	
Weight				kg	47	63		
Outdoor unit	Model name			PU-3VAKD/PU-3YJC		PU-5YAKD		
	External finish			Munsell 3Y 7.8/1.1				
	Refrigerant (R-22) control			Capillary tube				
	Compressor output	50Hz		kW	(V) 2.5, (Y) 2.4		3.5	
	Protection devices			(V): Internal thermostat (Y): Thermal switch, HP switch, LP switch, Thermal relay, Anti-phase protector		Internal thermostat, HP switch, LP switch, Thermal switch, Anti-phase protector		
	Fan motor output			kW	(V) 0.075, (Y) 0.085		0.10 + 0.10	
	Airflow	50Hz		CMM (CFM)	(V) 49 (1,730), (Y) 50 (1,765)		100 (3,530)	
	Noise level	50Hz		dB (A)	(V) 53, (Y) 52		55	
	Dimensions	W		mm	(V) 840, (Y) 870		970	
		D		mm	(V) 330, (Y) 295		345	
		H		mm	850		1,258	
	Weight				kg	(V) 74, (Y) 73	119	