

PK-GAKLD/FAKLD Wall mounted

Models				PK-1.6GAKLD	PK-2GAKLD	PK-2.5FAKLD	PK-3FAKLD	PK-4FAKLD
Cooling capacity* 1	50Hz	W		3,900	5,500	6,800	(V) 7,700, (Y) 7,900	10,100
		BTU/h		13,300	18,800	23,200	(V) 26,300, (Y) 27,000	34,500
Total input (50Hz) * 2		kW		1.49	1.88	2.31	(V) 3.29, (Y) 3.28	(V) 3.58, (Y) 3.51
Indoor unit	Model name			PK-1.6GAKLD	PK-2GAKLD	PK-2.5FAKLD	PK-3FAKLD	PK-4FAKLD
	External finish			Munsell 3.4Y 7.7/0.8 (white)				
	Fan motor output		kW	0.03			0.04	0.07
	Airflow (low-high)	50Hz	CMM	9-12	9-12	15-20	22-28	
			CFM	318-424	318-424	530-706	777-989	
	External static pressure		Pa (mmAq)	0 (direct blow)				
	Operation control & thermostat			Wireless remote controller & Built-in				
	Noise level (low-high)	50Hz	dB (A)	36-43	36-43	39-45	41-46	
	Unit drain pipe O.D.			mm				
	Dimensions	W	mm	990			1,400	1,680
		D					235	
H					340			
Weight		kg	16			24	28	
Outdoor unit	Model name			PU-1.6VLJA	PU-2VAKD	PU-2.5VAKD	PU-3VAKD/PU-3YJC	PU-4V/YAKD
	External finish			Munsell 7Y 7.8/1.1				
	Refrigerant (R-22) control			Capillary tube				
	Compressor output	50Hz	kW	1.2	1.5	1.7	(V) 2.5, (Y) 2.4	2.7
	Protection devices			(V): Internal thermostat (Y): Thermal switch, HP switch, LP switch, Thermal relay, Anti-phase protector				(V): Internal thermostat, HP switch (Y): Thermal switch, HP switch, Thermal relay, Anti-phase protector
	Fan motor output		kW	0.065	0.050	0.060	(V) 0.075, (Y) 0.085	0.065 + 0.065
	Airflow	50Hz	CMM (CFM)	45 (1,588)	38 (1,340)	39 (1,380)	(V) 49 (1,730), (Y) 50 (1,765)	95 (3,350)
	Noise level	50Hz	dB (A)	49	50	52	(V) 53, (Y) 52	54
	Dimensions	W	mm	870		850	(V) 840, (Y) 870	870
		D		295		290	(V) 330, (Y) 295	295
		H		650		605	850	1,258
Weight		kg	45	45	52	(V) 74, (Y) 73	94	