

PL-KAKD/KAKL Compact ceiling cassette

Models				PL-1.6KAKD/KAKL	PL-2KAKD/KAKL	PL-2.5KAKD/KAKL
Cooling capacity* ¹	50Hz	W	3,800	5,300	6,400	
		BTU/h	13,000	18,100	21,800	
Total input (50Hz) ** ²		kW	1.54	1.94	2.34	
Indoor unit	Model name		PL-1.6KAKD/KAKL	PL-2KAKD/KAKL	PL-2.5KAKD/KAKL	
	External finish		Galvanized sheets with gray heat insulation			
	Fan motor output		kW	0.03		
	Airflow (low-high)	50Hz	CMM	13-15	13-16	14-17
			CFM	460-530	460-565	495-600
	External static pressure		Pa (mmAq)	0 (direct blow)		
	Operation control & thermostat		Remote controlled & Built-in			
	Noise level (low-high)	50Hz	dB (A)	31-35	32-37	35-39.5
	Unit drain pipe I.D.		mm	32		
	Dimensions	W	mm	660		
		D		660		
		H		253		
Weight		kg	19	20		
Indoor grille	External finish		Munsell 0.70Y 8.59/0.97			
	Dimensions	W	760			
		D	760			
		H	30			
Weight		kg	3.7			
Outdoor unit	Model name		PU-1.6VLJA	PU-2VAKD	PU-2.5VAKD	
	External finish		Munsell 3Y 7.8/1.1			
	Refrigerant (R-22) control		Capillary tube			
	Compressor output	50Hz	kW	1.2	1.7	
	Protection devices		Internal thermostat, HP switch, LP switch		Internal thermostat	
	Fan motor output		kW	0.065	0.050	0.060
	Airflow	50Hz	CMM (CFM)	45 (1,588)	38 (1,340)	39 (1,380)
	Noise level	50Hz	dB (A)	49	50	52
	Dimensions	W	mm	870		
		D		295		
H		650				
Weight		kg	45	52		