

# PS-GAKD Floor standing

Models			PS-3GAKD	PS-4GAKD	PS-5GAKD	PS-6GAKD	
Cooling capacity*1	50Hz	W	7,700	9,800	12,400	14,800	
		BTU/h	26,300	33,400	42,300	50,500	
Total input (50Hz) **2		kW	(V) 3.33, (Y) 3.32	(V) 3.69, (Y) 3.62	4.33	5.40	
Indoor unit	Model name		PS-3GAKD	PS-4GAKD	PS-5GAKD	PS-6GAKD	
	External finish		Munsell 0.70Y 8.59/0.97				
	Fan motor output		kW	0.03	0.07	0.11	0.12
	Airflow (Low-High)	50Hz	CMM	14-17	22-28	23-31	25-32
			CFM	494-600	776-988	812-1,094	882-1,130
	External static pressure		Pa (mmAq)	0 (direct blow)			
	Operation control & thermostat		Built-in				
	Noise level (Low-High)	50Hz	dB (A)	37-42	42-47	43-49	45-50
	Unit drain pipe O.D.		mm	20			
	Dimensions	W	mm	600			
		D	mm	270	350		
		H	mm	1,900			
Weight		kg	43	51		53	
Outdoor unit	Model name		PU-3VAKD/PU-3YJC	PU-4V/YAKD	PU-5YAKD	PU-6YAKD	
	External finish		Munsell 3Y 7.8/1.1				
	Refrigerant (R-22) control		Capillary tube				
	Compressor output	50Hz	kW	(V) 2.5, (Y) 2.4	2.7	3.5	4.2
	Protection devices		(V): Internal thermostat (Y): Thermal switch, HP switch, LP switch, Thermal relay, Anti-phase protector	(V): Internal thermostat, HP switch (Y): Thermal switch, HP switch, Thermal relay, Anti-phase protector	Thermal switch, HP switch, LP switch, Anti-phase protector		
	Fan motor output		kW	(V) 0.075, (Y) 0.085	0.065 + 0.065	0.10 + 0.10	0.10 + 0.10
	Airflow	50Hz	CMM (CFM)	(V) 49 (1,730), (Y) 50 (1,765)	95 (3,350)	100 (3,530)	100 (3,530)
	Noise level	50Hz	dB (A)	(V) 53, (Y) 52	54	55	56
	Dimensions	W	mm	(V) 840, (Y) 870	870	970	
		D	mm	(V) 330, (Y) 295	295	345	
		H	mm	850	1,258	1,258	
	Weight		kg	(V) 74, (Y) 73	94	119	120