

Wall-mounted type MS-C series

Model	Indoor		MS-C08VC	MS-C10VC	MS-C13VC	MS-C18VC	MS-C24VD
	Outdoor		MU-C08VC	MU-C10VC	MU-C13VC	MU-C18VC	MU-C24VD
Function			Cooling				
Capacity	kW		2.30	2.75	3.50	5.20	6.90
	Btu/h		7,848	9,383	11,942	17,742	23,543
Power supply			220-230-240V, Single phase, 50Hz				
Power input	kW		0.70-0.72-0.74	0.84-0.87-0.9	1.15-1.19-1.22	1.72-1.79-1.86	2.60-2.64-2.68
EER (Btu/h.W)			11.21-10.90-10.61	11.17-10.79-10.43	10.38-10.04-9.79	10.30-9.93-9.55	9.04-8.91-8.77
Starting current	A		15.5-16-16.5	19-20-21	22-23.5-25	40-42-44	70-73-75
Running current	A		3.35-3.35-3.35	3.90-3.90-3.90	5.45-5.49-5.53	8.23-8.46-8.81	12.31-12.21-12.41
Air flow (Hi)	m ³ /min		10.4	11.5	11.6	14.6	14.7
Dimension (W X D X H)	Indoor	mm	788 X 225 X 295			780 X 210 X 298	1,100 X 258 X 325
	Outdoor	mm	684 X 255 X 540			800 X 285 X 550	850 X 290 X 605
Net Weight	Indoor	kg	9				16
	Outdoor	kg	22		25	35	55
Noise Level (Lo-Hi)	dB(A)		26-39	26-40	29-42	33-48	37-45
Connection method			Flared				
Dehumidification	l/h		1.0	1.2	1.6	2.3	3.5
Pipe size (Outer diameter)	Gas	mm	9.52		12.70		15.88
	Liquid	mm	6.35				
Max. piping length	m		20			30	
Max. height difference	m		10				