

Wall-mounted type MS-GC series

Model	Indoor		MS-GC10VD	MS-GC13VD
	Outdoor		MU-GC10VD	MU-GC13VD
Function		Cooling		
Capacity		kW	2.75	3.65-3.65-3.70
		Btu/h	9383	12454-12454-12624
Power supply		220-230-240V, Single phase, 50Hz		
Power input		kW	0.825-0.85-0.87	1.20-1.24-1.29
EER (Btu/h.W)			11.37-11.04-10.79	10.38-10.04-9.79
Starting current		A	15.5-16.5-17.5	24-25.5-27
Running current		A	3.87-3.85-3.82	5.62-5.71-5.79
Air flow (Hi)		m ³ /min	9.5-8.5	10.5-9.4
Dimension (W X D X H)	Indoor	mm	815 X 244 X 278	
	Outdoor	mm	684 X 255 X 540	
Net Weight	Indoor	kg	9	10
	Outdoor	kg	22	25
Noise Level (Lo-Hi)		dB(A)	26-39	29-42
Connection method		Flared		
Dehumidification		l/h	1.2	1.7
Pipe size (Outer diameter)	Gas	mm	9.52	12.7
	Liquid	mm	6.35	
Max. piping length		m	20	
Max. height difference		m	10	